

LIVOLTEK



Inversor Híbrido

Trifásico: HP3-5K/6K/8K/10K/12K/15K/17K/20K /25K/30K D1


Como núcleo de la solución de almacenamiento de energía, el inversor híbrido trifásico LIVOLTEK ofrece soluciones flexibles y escalables para aplicaciones residenciales y comerciales.

Con la capacidad de almacenamiento de batería escalable, el inversor de alto voltaje facilita un potente respaldo de energía y también presenta un alto autoconsumo con EMS integrado optimizado para reducir el costo de energía.



Características


- 150% PV sobredimensionado
- Salida 100% desequilibrada
- Máx. Corriente de entrada de CC de 20 A por cadena
- Monitoreo y mantenimiento en línea gratuitos
- Tiempo de conmutación de nivel de UPS para cargas críticas
- Modos de trabajo múltiples para un rendimiento óptimo



Configuración flexible
para carga



Rango de Voltaje
150V-800V



Soporte de carga
no balanceada




Limitación de exportación

Productos compatibles



Batería de litio de alto voltaje



Wi-Fi Dongle



Medidor Inteligente



Sistema de monitoreo

Especificaciones

Model	HP3-5KD1	HP3-6KD1	HP3-8KD1	HP3-10KD1	HP3-12KD1	HP3-15KD1	HP3-17KD1	HP3-20KD1	HP3-25KD1	HP3-30KD1
PV Input										
Max. PV Input Power	7500Wp	9000Wp	12000Wp	15000Wp	18000Wp	22500Wp	25500Wp	30000Wp	37500Wp	45000Wp
Max. PV Input Voltage	1000V									
Nominal Input Voltage	600V									
MPPT Voltage Range	150 V ~ 850 V									
No. of MPPTs/Strings per MPPT	2/(1+1)	2/(1+1)	2/(1+1)	2/(1+1)	2/(1+1)	2/(1+2)	2/(2+2)	2/(2+2)	2/(2+2)	2/(2+2)
Max.PV Current	20/20A	20/20A	20/20A	20/20A	20/20A	20/32A	32/32A	32/32A	40/40A	40/40A
Max. Short Circuit Current	30/30A	30/30A	30/30A	30/30A	30/30A	30/48A	48/48A	48/48A	60/60A	60/60A
AC Output @ Grid										
Nominal AC Output Power	5000W	6000W	8000W	10000W	12000W	15000W	17000W	20000W	25000W	30000W
Max. AC Input Power	7500W	9000W	12000W	15000W	18000W	22500W	25500W	30000W	37500W	45000W
Nominal AC Voltage	3W+N+PE, 230/400V									
AC Frequency	50 Hz / 60 Hz									
Max. Output Current	8.5A	10.5A	13.5A	17.0A	21.5A	27.0A	30.0A	32.0A	40.0A	48.0A
THDi,Rated Power[%]	< 3%									
Power Factor	~1 (Adjustable from 0.8 Leading to 0.8 Lagging)									
EPS Output @ Off Grid										
Nominal EPS Power	5000W	6000W	8000W	10000W	12000W	15000W	17000W	20000W	25000W	30000W
EPS Peak Power	1.1 x Pnom, 60sec									
Nominal Output Voltage	3W+N+PE, 230/400V									
Nominal Frequency	50 Hz/60 Hz									
Nominal Output Current	7.3A	8.7A	11.6A	14.5A	17.4A	21.8A	24.8A	29.0A	36.3A	43.5A
THDv,Rated Power[%]	< 3%									
Battery Input										
Battery Type	Lithium									
Battery Voltage Range	150V ~ 800 V									
Max. Charge/Discharge Current	30A/30A					50A/50A			60A / 60A	
Communication with BMS	CAN									
Efficiency										
Max. Efficiency	98.1%	98.1%	98.2%	98.2%	98.3%	98.3%	98.3%	98.3%	98.5%	98.5%
Euro Efficiency	97.5%	97.5%	97.5%	97.5%	97.6%	97.6%	97.8%	97.8%	98%	98.1%
General Data										
Dimension (W*H*D)	560*430*250 mm									
Weight	20kg	20kg	23kg	23kg	23kg	29kg	29kg	29kg	29kg	29kg
Mounting Method	Wall-mounted									
Protection Rating	IP65									
Cooling	Natural Convection		Intelligent Fan							
Operating Temperature Range	-25 °C~+60 °C									
Display	LED & APP									
Communication	Wi-Fi/DRM/CAN/RS485									
Standard Warranty	5 Years									

Remarks: The range of output Voltage and frequency may vary depending upon different grid codes.