


PNGMH72-B6(166) 440-460 Watt

HALF-CELL MBB MONO PERC



Key Features



Multi Busbar Solar Cell

Stronger current collection ability, Special circuit design with much lower hot spot temperature;



PID Resistant

Excellent PID resistance at 96 hours (85°C/85%) test, and also can be improved to meet higher standards for the particularly harsh environment;



Anti-Crack

Excellent anti-microcracking performance with more balanced interior stress;



Module efficiency up to 21.16%

Half cell structure brings low resistance characteristic, higher lifetime generating capacity, simultaneously lower annual power attenuation;



Low-Light Performance

Excellent power generation performance under Low-Light condition due to multi busbar; better shading response benefit from half cell module;




Strength and Durability

Certified for 5400Pa snow and 2400Pa Wind loads test;

Linear Performance Warranty

12 Years Product Warranty · 30 Years Linear Power Warranty



Certifications

- IEC 61215, IEC 61730, CE, CQC
- ISO9001: 2015: Quality management system
- ISO14001: 2015: Environmental management system
- ISO45001: 2018: Occupational health and safety management system



Electrical Specifications

Module Type: PNGMH72-B6-xxx, (xxx=Pmax)

Module Type	440		445		450		455		460	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Max. Power (Pmax/W)	440	330	445	334	450	338	455	341	460	345
Voltage at Max. Power (Vmp/V)	40.9	38.0	41.1	38.2	41.3	38.4	41.5	38.6	41.7	38.8
Current at Max. Power (Imp/A)	10.76	8.66	10.83	8.73	10.90	8.79	10.97	8.83	11.03	8.89
Open circuit voltage (Voc/V)	49.8	45.6	50.0	45.8	50.2	46.0	50.4	46.2	50.6	46.4
Short circuit current (Isc/A)	11.29	9.31	11.33	9.38	11.41	9.44	11.48	9.48	11.58	9.55
Module efficiency (%)	20.24%		20.47%		20.70%		20.93%		21.16%	
Power Tolerance (W)	0~+5									

Standard Test Condition (STC): Irradiance 1000W/m², Cell Temperature 25 °C, AM1.5

Nominal Module Operating Temperature (NOCT): Irradiance 800W/m², Ambient Temperature 20 °C, AM1.5, Wind Speed 1m/s


Mechanical Specifications

Cell Type	9BB MONO 166×83mm
No. of Cells	144 (6×24)
Dimension	2094x1038x35mm
Weight	24.5kg
Glass	3.2mm, Low Iron Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, 3 diodes
Output Cables	4mm ² , Length 300mm or customized
Connector type	MC4 compatible

Packaging Configurations

Per Pallet	31 pcs
Per 40' HQ Container	682 pcs

Engineering Drawings



Temperature Characteristics

NOCT Temperature	44 °C ±2 °C
Temperature Coefficient (Pmax)	-0.36%/ °C
Temperature Coefficient (Voc)	-0.28%/ °C
Temperature Coefficient (Isc)	0.05%/ °C

Maximum Ratings

Maximum system voltage (IEC)	1500V DC
Snow / Wind	5400Pa / 2400Pa
Operating Temperature	-40 °C ~ +85 °C
Maximum series fuse rating	20A

Curve & Temperature Dependence

